



LOAD RATING
135 kg

MODEL SHOWN
RS10

Mobile Rolling Steps are suitable for a multitude of applications but are most often used to access storage shelving in factories and warehouses

- ▶ Manufactured from welded steel
- ▶ Electro-galvanized finish as standard
- ▶ Double handrails, 25 mm tubing
- ▶ Extra-large top step with guardrail
- ▶ Slip resistant expanded metal treads
- ▶ Step height of 250 mm
- ▶ Step at an inclination angle of 60°
- ▶ 200 mm rubber wheels at rear for added stability and ease of movement
- ▶ Large base for added stability
- ▶ 100 mm lockable swivel castors in front for maneuverability and stability
- ▶ Collapsible for easy transport and storage
- ▶ Maximum platform height – 3.75 mm

OPTIONS

- ▶ Aluminium – up to 10 step unit

MODEL	RS3	RS4	RS6	RS8	RS10	RS12	RS15
Number of steps	3	4	6	8	10	12	15
Step width (mm)	405	585	590	590	590	590	590
Top step depth (mm)	365	365	365	365	365	365	365
Top step height (m)	0.85	1.10	1.60	2.10	2.60	3.10	3.85
Overall height (m)	1.75	2.00	2.50	3.00	3.50	4.00	4.75
Overall length (m)	0.85	1.05	1.35	1.70	1.95	2.35	2.80
Overall width (m)	0.82	1.15	1.15	1.07	1.07	1.07	1.07

